

Butoject® 898



APPLICATION

- › printing industry
- › laboratories
- › manufacturing of paints and varnishes
- › chemical industry
- › metal and plastics processing
- › recycling and waste disposal
- › cleaning and maintenance
- › fire brigades and forces

QUALITIES AND ADVANTAGES

- › very good protection against extremely aggressive chemicals
- › excellent wearing comfort
- › very good temperature flexibility
- › good mechanical resistance
- › high tightness against gas



Article no.	898
Name	Butoject® 898
Material	butyl
Description	rolled edge smooth, powdered
Length (mm)	340-360
Total thickness (mm)	0,7 ± 0,10
Colour	black
Size	8, 9, 10, 11
Classification	category III 0010 BCI



FEATURES

- › AQL < 0,65
- › excellent low degradation
- › manufactured by Vulkoject process technology
- › gastight (meets NATO requirements)
- › wide shape makes it possible to wear gloves underneath
- › may be reused for certain chemical groups after a special cleaning process (please consult the KCL-laboratory)
- › can be combined with chemical protective clothing

www.kcl.de
sales@kcl.de



by Honeywell

KCL GmbH

Industriepark Rhoen
 Am Kreuzacker 9
 36124 Eichenzell
 Germany
 Phone +49 6659 87-300
 Fax +49 6659 87-318